

KleanRite™ K2 and K3 Vacuums

The KleanRite™ K² and K³ line of vacuums feature strong, solid construction and cutting-edge innovations such as an electronic keypad with LED indicators that monitor the performance of the main and HEPA filters.

Designed to meet a wide range of industrial cleaning challenges, the two-motor K² comes with a 50 liter (13 gallon) collection container, while the K³, three-motor machine, is available with 50 or 100 liter (26 gallon) collection capacities. Extremely ergonomic, these vacuums feature a modular design for easy modifications, upgrades and servicing. The K² and K³ can be equipped with multi-stage filtration, including an optional HEPA filter to capture 99.97% of particulate, down to and including 0.3 microns.





KleanRite™ K2 Vacuum		
Power @ 60 HZ	2000	W
	2.68	HP
Waterlift, max	83.1	in. H2O
Airflow, max	198	CFM
Current, max (120V)	14.5	amps

KleanRite™ K3 Vacuum		
Power @ 60 HZ	2400	W
	3.22	HP
Waterlift, max	71.5	in. H2O
Airflow, max	270	CFM
Current, max (120V)	15.8	amps

KleanRite™ K3 Vacuum		
Power @ 60 HZ	3000	W
	4.2	HP
Waterlift, max	90	in. H2O
Airflow, max	314	CFM
Current, max (220V)	13	amps

